## Part number

# PEW 6383 SI





Flush-mounting plug, PLUSO series, 2 poles + PE, 8 h (white), 63 A, > 250 V

Product description	
Product type	Plug Flush-mounting
Series	PEWSI, PLUSO
N. of poles	2 poles + 🕒
Clock position	8
Technical data	
Current	63 A
Voltage	> 250 V
IP degree of protection	IP67
Further technical details	
Operating temperature range (min, max)	-25°C +40°C


Material properties	
Colour	RAL 7035 grey, RAL 9010 white
Approvals / Standards	
Reference standard	EN 60309-1 and -2
General ordering information	
AN13 code	8015747158407


#### Part number


# PEW 6383 SI



### Catalogue drawings







### **Notes**

Dimensions shown in mm are not binding and may be changed without notice.

- Compliant with EN 60309-1 and -2  $\,$
- Enclosure, insert and locking ring in insulating, thermoplastic, self-extinguishing material
- Flange with anti-ageing gasket
- PE...SI types (IP44), RAL 7035 grey enclosure, plug mouth colour coded according to the operating voltage
- PEW...SI (IP67) types, RAL 7035 grey enclosure, locking ring with gasket colour coded according to the operating voltage
- Terminals with retained screws
- 63A, 125A: with pilot contact
- Nickel-plated contacts, available on request for 16A and 32A (standard on 63A and 125A). For the code of products with nickel-plated contacts (socket holes, plug pins), add "N" to the pre-code of the corresponding standard product code; for example: PE becomes PEN and PEW becomes PEWN.
- IP44 and IP67 degrees of protection (EN 60529)