

Part number

# PK 12575 PB5



Interlocked switched socket-outlet, PK series,  
3 poles + N + PE, 7 h (black), 125 A, 480 ÷  
500 V, NH00 fuse carrier

#### Product description

|                       |                                    |
|-----------------------|------------------------------------|
| <b>Product type</b>   | Interlocked switched socket-outlet |
| <b>Series</b>         | PK..PB5                            |
| <b>N. of poles</b>    | 3 poles + N +                      |
| <b>Clock position</b> | 7                                  |
| <b>Specification</b>  | NH00 fuse carrier                  |

#### Technical data

|                                |             |
|--------------------------------|-------------|
| <b>Current</b>                 | 125 A       |
| <b>Voltage</b>                 | 480 ÷ 500 V |
| <b>IP degree of protection</b> | IP55        |

#### Further technical details

|  |                 |
|--|-----------------|
| <b>Weight</b>                                  | 9.200,00 g      |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C |
| <b>IK rating (impact degree of protection)</b> | IK10            |

#### Material properties

|                              |  |
|------------------------------|--|
| <b>Colour</b>                | RAL 7035 grey, RAL 9005 black  |
| <b>RoHs conformity</b>       | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| <b>China RoHs - EFUP</b>     | 50   |
| <b>REACH SVHC substances</b> | Yes<br>Lead  |
| <b>SCIP number</b>           | Ce861c8d-b979-403b-96d9-80aef6dc281d   |

#### Approvals / Standards

|                           |                     |
|---------------------------|---------------------|
| <b>Reference standard</b> | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747079549 |
|-------------------|---------------|

#### Packaging Information

|                              |                       |
|------------------------------|-----------------------|
| <b>Packaging length</b>      | 570,00 mm             |
| <b>Packaging height</b>      | 200,00 mm             |
| <b>Packaging width</b>       | 265,00 mm             |
| <b>Packaging weight</b>      | 9,90 kg               |
| <b>Packaging volume</b>      | 30,21 dm <sup>3</sup> |
| <b>Packaging description</b> | Carton box            |
| <b>Packaging quantity</b>    | 1 Pcs                 |
| <b>Packaging EAN code</b>    | 8015747079556         |
| <b>Sub-packaging length</b>  | 113,00 mm             |
| <b>Sub-packaging height</b>  | 36,00 mm              |
| <b>Sub-packaging width</b>   | 180,00 mm             |
| <b>Sub-packaging volume</b>  | 0,73 dm <sup>3</sup>  |

Part number

# PK 12575 PB5



## Catalogue drawings



## Notes

Dimensions shown in mm are not binding and may be changed without notice.