

Part number

PK 32114 EB



Interlocked switched socket-outlet, PK series, 3 poles + PE, 11 h (red), 32 A, 440 ÷ 460 V, without fuse-carrier

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7035 grey, RAL 3000 red
Series	PK..EB		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles +	RoHs conformity	50
Clock position	11	China RoHs - EFUP	50
Specification	Without fuse-carrier	REACH SVHC substances	Yes Lead
Technical data		SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Current	32 A	Approvals / Standards	
Voltage	440 ÷ 460 V	Reference standard	EN 60309-1, -2 e -4
IP degree of protection	IP44	General ordering information	
Further technical details		EAN13 code	8015747080927
Weight	1.300,00 g	Packaging Information	
Operating temperature range (min, max)	-25°C ... +40°C	Sub-packaging length	290,00 mm
IK rating (impact degree of protection)	IK10	Sub-packaging height	125,00 mm
		Sub-packaging width	155,00 mm
		Sub-packaging weight	1,30 kg
		Sub-packaging volume	5,62 dm ³
		Sub-packaging description	Carton box
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747080934

Part number

PK 32114 EB



Catalogue drawings



Notes

Dimensions shown in mm are not binding and may be changed without notice.