

Part number

# PK 3233 PB5



Interlocked switched socket-outlet, PK series,  
2 poles + PE, 3 h (white), 32 A, 50 ÷ 250 V,  
E33 - DIII fuse carrier

Product description		Material properties	
<b>Product type</b>	Interlocked switched socket-outlet	<b>Colour</b>	RAL 7035 grey, RAL 9010 white
<b>Series</b>	PK..PB5		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>N. of poles</b>	2 poles +	<b>RoHs conformity</b>	50
<b>Clock position</b>	3	<b>China RoHs - EFUP</b>	50
<b>Specification</b>	E33 - DIII fuse carrier	<b>REACH SVHC substances</b>	Yes Lead
Technical data		<b>SCIP number</b>	F6799547-ab84-42f2-938f-233ba663766d
<b>Current</b>	32 A	Approvals / Standards	
<b>Voltage</b>	> 50 ÷ 250 V	<b>Reference standard</b>	EN 60309-1, -2 e -4
<b>IP degree of protection</b>	IP55	General ordering information	
Further technical details		<b>EAN13 code</b>	8015747081061
<b>Weight</b>	3.425,00 g	Packaging Information	
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Packaging length</b>	400,00 mm
<b>IK rating (impact degree of protection)</b>	IK10	<b>Packaging height</b>	310,00 mm
		<b>Packaging width</b>	670,00 mm
		<b>Packaging weight</b>	27,40 kg
		<b>Packaging volume</b>	83,08 dm <sup>3</sup>
		<b>Packaging description</b>	Carton box
		<b>Packaging quantity</b>	8 Pcs
		<b>Packaging EAN code</b>	8015747081078
		<b>Sub-packaging length</b>	150,00 mm
		<b>Sub-packaging height</b>	140,00 mm
		<b>Sub-packaging width</b>	380,00 mm
		<b>Sub-packaging weight</b>	3,43 kg
		<b>Sub-packaging volume</b>	7,98 dm <sup>3</sup>
		<b>Sub-packaging description</b>	Carton box
		<b>Sub-packaging quantity</b>	1 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747081085

Part number

# PK 3233 PB5



## Catalogue drawings



	<b>A</b>
<b>2P+⊕</b>	<b>363</b>
<b>3P+⊕</b>	<b>370</b>
<b>3P+N+⊕</b>	<b>370</b>

## Notes

Dimensions shown in mm are not binding and may be changed without notice.