


Part number

# PN 1665 PI



Flush-mounting socket outlet, PLUSO LS-TYPE series, 3 poles + N + PE, 6 h (red), 16 A, 380 ÷ 415 V, inclined

Product description		Material properties	
<b>Product type</b>	Socket Flush-mounting	<b>Colour</b>	RAL 9005 black
<b>Series</b>	PN...PI, PLUSO LS-TYPE	<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>Connection type</b>	Screw terminal connection	<b>China RoHs - EFUP</b>	50
<b>N. of poles</b>	3 poles + N + 	<b>REACH SVHC substances</b>	Yes Lead
<b>Clock position</b>	6	<b>SCIP number</b>	Ca7de37f-add8-4b77-9861-279c94903ade
<b>Size</b>	Socket fixing centre distance 77 x 85 mm	<b>Approvals / Standards</b>	
<b>Specification</b>	Inclined	<b>Reference standard</b>	EN 60309-1 and -2
Technical data		General ordering information	
<b>Current</b>	16 A	<b>EAN13 code</b>	8015747190060
<b>Voltage</b>	380 ÷ 415 V	Packaging Information	
<b>IP degree of protection</b>	IP44	<b>Packaging length</b>	285,00 mm
Further technical details		<b>Packaging height</b>	170,00 mm
<b>Weight</b>	180,50 g	<b>Packaging width</b>	190,00 mm
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Packaging weight</b>	2,01 kg
		<b>Packaging volume</b>	9,21 dm <sup>3</sup>
		<b>Packaging description</b>	Carton box
		<b>Packaging quantity</b>	10 Pcs
		<b>Packaging EAN code</b>	8015747190077

Part number

**PN 1665 PI**



---

## Notes

Dimensions shown in mm are not binding and may be changed without notice.

- 
- Enclosure and spring lid colour RAL 9005 black
  - Compliant with EN 60309-1 and -2
  - Enclosure, insert and spring lid in insulating, thermoplastic, self-extinguishing material
  - Flange with anti-ageing gasket
  - PN...PI - PN...PQ types (IP44), spring lid
  - Terminals with retained screws
  - IP44 degree of protection (EN 60529)
-