


Part number

PN 3263 PV



Mobile socket outlet, PLUSO LS-TYPE series, 2 poles + PE, 6 h (blue), 32 A, 200 ÷ 250 V

Product description

Product type	Socket Mobile
Series	PN...SV, PLUSO LS-TYPE
Connection type	Screw terminal connection
N. of poles	2 poles + 
Clock position	6

Technical data

Current	32 A
Voltage	200 ÷ 250 V
IP degree of protection	IP44

Further technical details

Weight	1,00 g
Operating temperature range (min, max)	-25°C ... +40°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade

Approvals / Standards

Reference standard	EN 60309-1 and -2
---------------------------	-------------------

General ordering information

EAN13 code	8015747032865
-------------------	---------------

Packaging Information

Packaging length	330,00 mm
Packaging height	175,00 mm
Packaging width	295,00 mm
Packaging volume	17,04 dm ³
Packaging description	Carton box
Packaging quantity	10 Pcs
Packaging EAN code	8015747253024

Part number

PN 3263 PV



Notes

Dimensions shown in mm are not binding and may be changed without notice.

-
- PN...SV types 16A (IP44), entry with cable gland colour RAL 9005 black, enclosure colour RAL 9005 black
 - PN...PV types 16A (IP44), enclosure and spring lid colour RAL 9005 black, entry with cable gland
 - Compliant with EN 60309-1 and -2
 - PN...SV types, enclosure and insert in insulating, thermoplastic, self-extinguishing material
 - PN...PV types, enclosure, insert and spring lid in insulating, thermoplastic, self-extinguishing material
 - Terminals with retained screws
 - IP44 degree of protection (EN 60529)
-