


Part number

PN 3263 SV



Mobile plug, PLUSO LS-TYPE series, 2 poles + PE, 6 h (blue), 32 A, 200 ÷ 250 V, straight

Product description

Product type	Plug Mobile
Series	PN...SV, PLUSO LS-TYPE
N. of poles	2 poles + 
Clock position	6
Specification	Straight

Technical data

Current	32 A
Voltage	200 ÷ 250 V
IP degree of protection	IP44

Further technical details

Weight	1,00 g
Operating temperature range (min, max)	-25°C ... +40°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade

Approvals / Standards

Reference standard	EN 60309-1 and -2
---------------------------	-------------------

General ordering information

EAN13 code	8015747032773
-------------------	---------------

Packaging Information

Packaging length	285,00 mm
Packaging height	170,00 mm
Packaging width	190,00 mm
Packaging volume	9,21 dm ³
Packaging description	Carton box
Packaging quantity	10 Pcs
Packaging EAN code	8015747253017

Part number

PN 3263 SV



Notes

Dimensions shown in mm are not binding and may be changed without notice.

-
- PN...SV types 16A (IP44), entry with cable gland colour RAL 9005 black, enclosure colour RAL 9005 black
 - PN...PV types 16A (IP44), enclosure and spring lid colour RAL 9005 black, entry with cable gland
 - Compliant with EN 60309-1 and -2
 - PN...SV types, enclosure and insert in insulating, thermoplastic, self-extinguishing material
 - PN...PV types, enclosure, insert and spring lid in insulating, thermoplastic, self-extinguishing material
 - Terminals with retained screws
 - IP44 degree of protection (EN 60529)
-