


Part number

SQV 1633



Interlocked switched socket-outlet, SQV series, 2 poles + PE, 3 h (white), 16 A, 50 ÷ 250 V, sectionable fuse carrier 10 x 38 mm

| Product description | |
|--|---|
| Product type | Interlocked switched socket-outlet |
| Series | SQV |
| N. of poles | 2 poles +  |
| Clock position | 3 |
| Specification | Sectionable fuse carrier 10 x 38 mm |
| Technical data | |
| Current | 16 A |
| Voltage | > 50 ÷ 250 V |
| IP degree of protection | IP44 |
| Further technical details | |
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK08 |

| Material properties | |
|------------------------------|-------------------------------|
| Colour | RAL 7035 grey, RAL 9010 white |
| Approvals / Standards | |
| Reference standard | EN 60309-1, -2 e -4 |
| General ordering information | |
| EAN13 code | 8015747160193 |

Part number

SQV 1633



Catalogue drawings



Catalogue drawings



| SQV | | A |
|-----|--------|----|
| 16A | 2P+⊕ | 64 |
| | 3P+⊕ | 65 |
| | 3P+N+⊕ | 67 |

Notes

Dimensions shown in mm are not binding and may be changed without notice.