

Part number

TM 1645 IS



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 4 h (yellow), 16 A, 57/100 ÷ 75/130 V, sectionable fuse carrier 10 x 38 mm, with base box


Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7012 grey, RAL 1021 yellow
Series	TM.. IS/KIS	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles + N + 	China RoHs - EFUP	50
Clock position	4	REACH SVHC substances	Yes
Size	115 x 450 x 18 mm	Lead	Lead
Specification	Sectionable fuse carrier 10 x 38 mm With base box	SCIP number	Ce861c8d-b979-403b-96d9-80aef6dc281d
Technical data		Approvals / Standards	
Current	16 A	Reference standard	EN 60309-1, -2 e -4
Voltage	57/100 ÷ 75/130 V	General ordering information	
IP degree of protection	IP66 / IP67	EAN13 code	8015747089708
Further technical details		Packaging Information	
Weight	1.550,00 g	Packaging weight	14,02 kg
Operating temperature range (min, max)	-25°C ... +40°C	Packaging volume	55,44 dm³
UL 94 flammability rating	V-2	Packaging description	Carton box
IK rating (impact degree of protection)	IK10	Packaging quantity	9 Pcs
		Packaging EAN code	8015747204354
		Sub-packaging weight	1,56 kg
		Sub-packaging description	Plastic packaging
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747107006

Part number

TM 1645 IS



Catalogue drawings



Notes

Dimensions shown in mm are not binding and may be changed without notice.