


Part number

# TM 1695 IT



Interlocked switched socket-outlet, TM series,  
3 poles + N + PE, 9 h (blue), 16 A, 120/208 ÷  
144/250 V, E16 fuse carrier, with base box

| Product description                            |                                                                                                   |
|------------------------------------------------|---------------------------------------------------------------------------------------------------|
| <b>Product type</b>                            | Interlocked switched socket-outlet                                                                |
| <b>Series</b>                                  | TM.. IT                                                                                           |
| <b>N. of poles</b>                             | 3 poles + N +  |
| <b>Clock position</b>                          | 9                                                                                                 |
| <b>Size</b>                                    | 115 x 450 x 18 mm                                                                                 |
| <b>Specification</b>                           | E16 fuse carrier<br>With base box                                                                 |
| Technical data                                 |                                                                                                   |
| <b>Current</b>                                 | 16 A                                                                                              |
| <b>Voltage</b>                                 | 120/208 ÷ 144/250 V                                                                               |
| <b>IP degree of protection</b>                 | IP66 / IP67                                                                                       |
| Further technical details                      |                                                                                                   |
| <b>Weight</b>                                  | 1.630,00 g                                                                                        |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C                                                                                   |
| <b>UL 94 flammability rating</b>               | V-2                                                                                               |
| <b>IK rating (impact degree of protection)</b> | IK10                                                                                              |

| Material properties              |                              |
|----------------------------------|------------------------------|
| <b>Colour</b>                    | RAL 7012 grey, RAL 5015 blue |
| Approvals / Standards            |                              |
| <b>Reference standard</b>        | EN 60309-1, -2 e -4          |
| General ordering information     |                              |
| <b>EAN13 code</b>                | 8015747090575                |
| Packaging Information            |                              |
| <b>Sub-packaging weight</b>      | 1,63 kg                      |
| <b>Sub-packaging description</b> | Plastic packaging            |
| <b>Sub-packaging quantity</b>    | 1 Pcs                        |
| <b>Sub-packaging EAN barcode</b> | 8015747107143                |

Part number

# TM 1695 IT



Catalogue drawings



|               | A   | B   |
|---------------|-----|-----|
| <b>2P+⊕</b>   | 133 | 276 |
| <b>3P+⊕</b>   | 135 | 276 |
| <b>3P+N+⊕</b> | 140 | 277 |

## Notes

Dimensions shown in mm are not binding and may be changed without notice.