

Part number

TM 3223KSSP



Interlocked switched socket-outlet, TM series,
2 poles + PE, 2 h (green), 32 A, > 50 V,
without fuse-carrier, without base box

Product description

Product type	Interlocked switched socket-outlet
Series	TM..SSP/KSSP
N. of poles	2 poles +
Clock position	2
Specification	Without fuse-carrier Without base box

Technical data

Current	32 A
Voltage	> 50 V
IP degree of protection	IP66 / IP67

Further technical details

Weight	1.060,00 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-2
IK rating (impact degree of protection)	IK10

Material properties

Colour	RAL 7012 grey, RAL 6017 green
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	Ce861c8d-b979-403b-96d9-80aef6dc281d

Approvals / Standards

Reference standard	EN 60309-1, -2 e -4
---------------------------	---------------------

General ordering information

EAN13 code	8015747162357
-------------------	---------------

Packaging Information

Packaging length	385,00 mm
Packaging height	320,00 mm
Packaging width	485,00 mm
Packaging weight	9,54 kg
Packaging volume	59,75 dm ³
Packaging description	Carton box
Packaging quantity	9 Pcs
Packaging EAN code	8015747036450
Sub-packaging length	95,00 mm
Sub-packaging height	40,00 mm
Sub-packaging width	253,00 mm
Sub-packaging weight	1,06 kg
Sub-packaging volume	0,96 dm ³
Sub-packaging description	Carton tray
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747084161

Part number

TM 3223KSSP



Notes

Dimensions shown in mm are not binding and may be changed without notice.
