


Part number

TM 3225KSSP



Interlocked switched socket-outlet, TM series,
3 poles + N + PE, 2 h (green), 32 A, > 50 V,
without fuse-carrier, without base box

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM..SSP/KSSP |
| N. of poles | 3 poles + N +  |
| Clock position | 2 |
| Specification | Without fuse-carrier Without base box |

Technical data

| | |
|--------------------------------|-------------|
| Current | 32 A |
| Voltage | > 50 V |
| IP degree of protection | IP66 / IP67 |

Further technical details

| | |
|--|-----------------|
| Weight | 1.200,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-2 |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|------------------------------|---|
| Colour | RAL 7012 grey |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ce861c8d-b979-403b-96d9-80aef6dc281d |

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747162616 |
|-------------------|---------------|

Packaging Information

| | |
|----------------------------------|-----------------------|
| Packaging length | 385,00 mm |
| Packaging height | 320,00 mm |
| Packaging width | 485,00 mm |
| Packaging weight | 11,20 kg |
| Packaging volume | 59,75 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 9 Pcs |
| Packaging EAN code | 8015747084178 |
| Sub-packaging length | 95,00 mm |
| Sub-packaging height | 40,00 mm |
| Sub-packaging width | 253,00 mm |
| Sub-packaging weight | 1,24 kg |
| Sub-packaging volume | 0,96 dm ³ |
| Sub-packaging description | Carton tray |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747084192 |

Part number

TM 3225KSSP



Notes

Dimensions shown in mm are not binding and may be changed without notice.
