


Part number

TM 3264 IR



Interlocked switched socket-outlet, TM series, 3 poles + PE, 6 h (red), 32 A, 380 ÷ 415 V, with compartment for modular units, 6 DIN-rail modules EN 60715, with base box

| Product description | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM..IR/KIR |
| N. of poles | 3 poles +  |
| Clock position | 6 |
| Size | 145 x 565 x 18 mm |
| Specification | With compartment for modular units, 6 DIN-rail modules EN 60715 With base box |

| Technical data | |
|--------------------------------|-------------|
| Current | 32 A |
| Voltage | 380 ÷ 415 V |
| IP degree of protection | IP66 / IP67 |

| Further technical details | |
|--|-----------------|
| Weight | 2.910,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-2 |
| IK rating (impact degree of protection) | IK10 |

| Material properties | |
|------------------------------|--|
| Colour | RAL 7012 grey, RAL 3000 red |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | F6799547-ab84-42f2-938f-233ba663766d |

| Approvals / Standards | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |

| General ordering information | |
|------------------------------|---------------|
| EAN13 code | 8015747091916 |

| Packaging Information | |
|----------------------------------|-----------------------|
| Sub-packaging length | 150,00 mm |
| Sub-packaging height | 188,00 mm |
| Sub-packaging width | 430,00 mm |
| Sub-packaging weight | 2,91 kg |
| Sub-packaging volume | 12,13 dm ³ |
| Sub-packaging description | Carton box |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747091930 |

Part number

TM 3264 IR



Catalogue drawings



| | A |
|---------------|----------|
| 2P+⊕ | 162 |
| 3P+⊕ | 162 |
| 3P+N+⊕ | 169 |

Notes

Dimensions shown in mm are not binding and may be changed without notice.