

Part number

TM 3293KSIR



Interlocked switched socket-outlet, TM series, 2 poles + PE, 9 h (red), 32 A, 380 ÷ 415 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, without base box

Product description	
Product type	Interlocked switched socket-outlet
Series	TM...SIR/KSIR
N. of poles	2 poles + 
Clock position	9
Size	114 x 255 mm fixing distance, for assembly in single or multiple boxes
Specification	With compartment for modular units, 4,5 DIN-rail modules EN 60715 Without base box
Technical data	
Current	32 A
Voltage	380 ÷ 415 V
IP degree of protection	IP66 / IP67
Further technical details	
Weight	1.080,00 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-2
IK rating (impact degree of protection)	IK10


Material properties	
Colour	RAL 7012 grey, RAL 3000 red
Approvals / Standards	
Reference standard	EN 60309-1, -2 e -4
General ordering information	
EAN13 code	8015747126205

Part number

TM 3293KSIR



Catalogue drawings



	A
2P+⊕	96
3P+⊕	96
3P+N+⊕	101

Notes

Dimensions shown in mm are not binding and may be changed without notice.