

Part number

TM 3295KSP



Interlocked switched socket-outlet, TM series,
3 poles + N + PE, 9 h (blue), 32 A, 120/208 ÷
144/250 V, without fuse-carrier, with base box


Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7012 grey, RAL 5015 blue
Series	TM..SP/KSP		Compliant with exemption
N. of poles	3 poles + N + 	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Clock position	9	China RoHs - EFUP	50
Size	115 x 450 x 18 mm	REACH SVHC substances	Yes
Specification	Without fuse-carrier With base box	Lead	Lead
SCIP number		Ce861c8d-b979-403b-96d9-80aef6dc281d	
Technical data		Approvals / Standards	
Current	32 A	Reference standard	EN 60309-1, -2 e -4
Voltage	120/208 ÷ 144/250 V	General ordering information	
IP degree of protection	IP66 / IP67	EAN13 code	8015747126342
Further technical details		Packaging Information	
Weight	1.450,00 g	Packaging length	385,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Packaging height	320,00 mm
UL 94 flammability rating	V-2	Packaging width	485,00 mm
IK rating (impact degree of protection)	IK10	Packaging weight	13,05 kg
		Packaging volume	59,75 dm³
		Packaging description	Carton box
		Packaging quantity	9 Pcs
		Packaging EAN code	8015747232814
		Sub-packaging weight	1,45 kg
		Sub-packaging description	Carton tray
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747232821

Part number

TM 3295KSP



Catalogue drawings



Notes

Dimensions shown in mm are not binding and may be changed without notice.