


Part number

TM 63114 IS



Interlocked switched socket-outlet, TM series, 3 poles + PE, 11 h (red), 63 A, 440 ÷ 460 V, sectionable fuse carrier 22 x 58 mm, with base box

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM.. IS/KIS |
| N. of poles | 3 poles +  |
| Clock position | 11 |
| Specification | Sectionable fuse carrier 22 x 58 mm With base box |

Technical data

| | |
|--------------------------------|-------------|
| Current | 63 A |
| Voltage | 440 ÷ 460 V |
| IP degree of protection | IP66 / IP67 |

Further technical details

| | |
|--|-------------------------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-0 (insert), V-2 (enclosure) |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|---------------|-----------------------------|
| Colour | RAL 7012 grey, RAL 3000 red |
|---------------|-----------------------------|

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information


| | |
|-------------------|---------------|
| EAN13 code | 8015747163422 |
|-------------------|---------------|

Part number

TM 63114 IS



Catalogue drawings



Notes

Dimensions shown in mm are not binding and may be changed without notice.