


Part number

# BE 3245



Interlocked switched socket-outlet, BE series, 3 poles + N + PE, 4 h (yellow), 32 A, 57/100 ÷ 75/130 V, without fuse-carrier

Product description		Material properties	
<b>Product type</b>	Interlocked switched socket-outlet	<b>Colour</b>	RAL 7035 grey, RAL 1021 yellow
<b>Series</b>	BE		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>N. of poles</b>	3 poles + N + 	<b>RoHs conformity</b>	6(c): copper alloy containing up to 4% lead by weight
<b>Clock position</b>	4	<b>China RoHs - EFUP</b>	50
<b>Size</b>	Socket centre distance 114 x 228 mm	<b>REACH SVHC substances</b>	Yes Lead
<b>Specification</b>	Without fuse-carrier	<b>SCIP number</b>	Ce861c8d-b979-403b-96d9-80aef6dc281d
Technical data		Approvals / Standards	
<b>Current</b>	32 A	<b>Reference standard</b>	EN 60309-1, -2 e -4
<b>Voltage</b>	57/100 ÷ 75/130 V	General ordering information	
<b>IP degree of protection</b>	IP67	<b>EAN13 code</b>	8015747003674
Further technical details		Packaging Information	
<b>Weight</b>	1.340,00 g	<b>Sub-packaging length</b>	116,00 mm
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Sub-packaging height</b>	130,00 mm
<b>IK rating (impact degree of protection)</b>	IK10	<b>Sub-packaging width</b>	230,00 mm
		<b>Sub-packaging weight</b>	1,34 kg
		<b>Sub-packaging volume</b>	3,47 dm <sup>3</sup>
		<b>Sub-packaging description</b>	Carton box
		<b>Sub-packaging quantity</b>	1 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747110648

Part number

**BE 3245**



---

Notes