

Part number

BT 16220



Socket-outlet with safety transformer, BT series, 2 poles, 16 A, 24 V, 220/24 V transformer

Product description

| | |
|-----------------------|---------------------------------------|
| Product type | Socket-outlet with safety transformer |
| Series | BT |
| N. of poles | 2 poles |
| Clock position | No key way |
| Size | Socket centre distance 114 x 228 mm |
| Specification | 220/24 V transformer |

Technical data

| | |
|--------------------------------|------|
| Current | 16 A |
| Voltage | 24 V |
| IP degree of protection | IP67 |

Further technical details

| | |
|--|-----------------|
| Weight | 2.485,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 4001 lilac |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | 8e89f7de-4d73-4bfd-b5c1-5e57c8f79fed |

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747005548 |
|-------------------|---------------|

Packaging Information

| | |
|----------------------------------|----------------------|
| Sub-packaging length | 116,00 mm |
| Sub-packaging height | 130,00 mm |
| Sub-packaging width | 230,00 mm |
| Sub-packaging weight | 2,49 kg |
| Sub-packaging volume | 3,47 dm ³ |
| Sub-packaging description | Carton box |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747005555 |

Part number

BT 16220



Notes