

Part number

# CCFA 4.0



Female crimp contact, CC series, 16 A, turned silver plated, wire cross section 4 mm<sup>2</sup>, AWG 12

| Product description                |                      | Material properties                 |   |
|------------------------------------|----------------------|-------------------------------------|---|
| <b>Product type</b>                | Crimp contact        | <b>Main material</b>                | Copper alloy  |
| <b>Series</b>                      | CC                   |                                     | Compliant with exemption                              |
| <b>Gender</b>                      | Female               | <b>RoHs conformity</b>              | 6(c): copper alloy containing up to 4% lead by weight |
| Technical data                     |                      | <b>China RoHs - EFUP</b>            | 50  |
| <b>Current</b>                     | 16 A                 | <b>REACH SVHC substances</b>        | Yes<br>Lead   |
| <b>Wire cross-section</b>          | 4,00 mm <sup>2</sup> | <b>SCIP number</b>                  | C0979fba-9907-458f-a94a-db781440f273                  |
| <b>AWG size</b>                    | 12                   | <b>Approvals / Standards</b>        |   |
| <b>Contact type</b>                | Turned silver plated | <b>Certifications</b>               | CSA, EAC  |
| Further technical details          |                      | <b>UL</b>                           | ECBT2   |
| <b>Weight</b>                      | 1,68 g               | <b>General ordering information</b> |   |
| <b>Conductors stripping length</b> | 7,5 mm               | <b>EAN13 code</b>                   | 8015747011754   |
|                                    |                      | <b>eCl@ss 8.1</b>                   | 27440204  |
|                                    |                      | <b>ETIM 7.0</b>                     | EC000796  |
|                                    |                      | <b>Packaging Information</b>        |   |
|                                    |                      | <b>Packaging length</b>             | 112,00 mm   |
|                                    |                      | <b>Packaging height</b>             | 95,00 mm  |
|                                    |                      | <b>Packaging width</b>              | 117,00 mm   |
|                                    |                      | <b>Packaging weight</b>             | 1,46 kg   |
|                                    |                      | <b>Packaging volume</b>             | 1,24 dm <sup>3</sup>                                  |
|                                    |                      | <b>Packaging description</b>        | Carton box  |
|                                    |                      | <b>Packaging quantity</b>           | 800 Pcs   |
|                                    |                      | <b>Packaging EAN code</b>           | 8015747103879   |
|                                    |                      | <b>Sub-packaging length</b>         | 50,00 mm  |
|                                    |                      | <b>Sub-packaging height</b>         | 44,00 mm  |
|                                    |                      | <b>Sub-packaging width</b>          | 50,00 mm  |
|                                    |                      | <b>Sub-packaging weight</b>         | 0,18 kg   |
|                                    |                      | <b>Sub-packaging volume</b>         | 0,11 dm <sup>3</sup>                                  |
|                                    |                      | <b>Sub-packaging description</b>    | Plastic box   |
|                                    |                      | <b>Sub-packaging quantity</b>       | 100 Pcs   |
|                                    |                      | <b>Sub-packaging EAN barcode</b>    | 8015747011761   |

Part number

# CCFA 4.0



## Catalogue drawings



### CCF, CCM and CC..AN contacts

| conductor section<br>$\text{mm}^2$ | conductor slot<br>$\varnothing A$ (mm) | conductors stripping length<br>(mm) |
|------------------------------------|--|-------------------------------------|
| 0,14-0,37                          | 0,9                                    | 7,5                                 |
| 0,5                                | 1,1                                    | 7,5                                 |
| 0,75                               | 1,3                                    | 7,5                                 |
| 1,0                                | 1,45                                   | 7,5                                 |
| 1,5                                | 1,8                                    | 7,5                                 |
| 2,5                                | 2,2                                    | 7,5                                 |
| 3                                  | 2,55                                   | 7,5                                 |
| 4                                  | 2,85                                   | 7,5                                 |

Notes

## California Proposition 65 Information



### **WARNING**

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

---