

Part number

CX 25 IF



Female modular insert, Mixo series, crimp connection, 25 poles, 1 module, 4 A 50 V 0,8 kV 3

Product description		Material properties	
Product type	Modular insert	Main material	Polycarbonate
Series	Mixo	Colour	RAL 7032 grey
Connection type	Crimp connection	RoHS conformity	Compliant
Gender	Female	China RoHS - EFUP	E
N. of poles	25 poles	REACH SVHC substances	No
Size	1 module		
Technical data		Approvals / Standards	
Current	4 A	Reference standard	EN 61984:2009-06
Voltage	50 V	Certifications	CSA, DNV, BV
Rated impulse withstand voltage	0,8 kV	UL	ECBT2
Pollution degree	3	cUL	ECBT8
Rated voltage according to UL/CSA	600 V		
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure	General ordering information	
		EAN13 code	8015747148313
Further technical details		Packaging Information	
Characteristics according to EN 61984	5A 50V 10A 3	Packaging length	180,00 mm
Insulation resistance	≥ 10 GΩ	Packaging height	120,00 mm
Contact resistance	≤ 4 mΩ	Packaging width	155,00 mm
Weight	8,80 g	Packaging weight	0,69 kg
Operating temperature range (min, max)	-40 °C ... +125 °C	Packaging volume	3,35 dm ³
UL 94 flammability rating	V-0	Packaging description	Carton box
		Packaging quantity	60 Pcs
		Packaging EAN code	8015747221351
		Sub-packaging length	35,00 mm
		Sub-packaging height	40,00 mm
		Sub-packaging width	155,00 mm
		Sub-packaging weight	0,12 kg
		Sub-packaging volume	0,22 dm ³
		Sub-packaging description	Carton tray
		Sub-packaging quantity	10 Pcs
		Sub-packaging EAN barcode	8015747148337

Part number

CX 25 IF



Notes