


Part number

# KI 16104 RI5



Interlocked switched socket-outlet, KI series, 3 poles + PE, 10 h (green), 16 A, > 50 V, with compartment for modular units, 7 DIN-rail modules EN 60715

Product description		Material properties	
<b>Product type</b>	Interlocked switched socket-outlet	<b>Colour</b>	RAL 7035 grey, RAL 6017 green
<b>Series</b>	KI..RI5		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>N. of poles</b>	3 poles + 	<b>RoHs conformity</b>	6(c): copper alloy containing up to 4% lead by weight
<b>Clock position</b>	10	<b>China RoHs - EFUP</b>	50
<b>Cable entry</b>	Pg29	<b>REACH SVHC substances</b>	Yes Lead
<b>Specification</b>	With compartment for modular units, 7 DIN-rail modules EN 60715	<b>SCIP number</b>	Ce861c8d-b979-403b-96d9-80aef6dc281d
Technical data		Approvals / Standards	
<b>Current</b>	16 A	<b>Reference standard</b>	EN 60309-1, -2 e -4
<b>Voltage</b>	> 50 V	General ordering information	
<b>IP degree of protection</b>	IP55	<b>EAN13 code</b>	8015747048231
Further technical details		Packaging Information	
<b>Weight</b>	1.720,00 g	<b>Packaging length</b>	400,00 mm
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Packaging height</b>	165,00 mm
<b>IK rating (impact degree of protection)</b>	IK10	<b>Packaging width</b>	170,00 mm
		<b>Packaging weight</b>	1,72 kg
		<b>Packaging volume</b>	11,22 dm <sup>3</sup>
		<b>Packaging description</b>	Carton box
		<b>Packaging quantity</b>	1 Pcs
		<b>Packaging EAN code</b>	8015747048248

Part number

# KI 16104 RI5



## Catalogue drawings



---

Notes