


Part number

KI 1674 IB6



Interlocked switched socket-outlet, IB6 series,
3 poles + PE, 7 h (black), 16 A, 480 ÷ 500 V,
sectionable fuse carrier 10 x 38 mm

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7035 grey, RAL 9005 black
Series	KI...IB6		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles + 	RoHs conformity	
Clock position	7	China RoHs - EFUP	50
Cable entry	M25	REACH SVHC substances	Yes Lead
Specification	Sectionable fuse carrier 10 x 38 mm	SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Technical data		Approvals / Standards	
Current	16 A	Reference standard	EN 60309-1, -2 e -4
Voltage	480 ÷ 500 V	General ordering information	
IP degree of protection	IP66	EAN13 code	8015747199445
Further technical details		Packaging Information	
Weight	950,00 g	Packaging length	520,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Packaging height	305,00 mm
IK rating (impact degree of protection)	IK10	Packaging width	490,00 mm
		Packaging weight	14,95 kg
		Packaging volume	77,71 dm ³
		Packaging description	Carton box
		Packaging quantity	15 Pcs
		Packaging EAN code	8015747229913
		Sub-packaging length	270,00 mm
		Sub-packaging height	125,00 mm
		Sub-packaging width	120,00 mm
		Sub-packaging weight	1,00 kg
		Sub-packaging volume	4,05 dm ³
		Sub-packaging description	Carton box
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747229920

Part number

KI 1674 IB6



Notes