


Part number

KI 3245 IB6



Interlocked switched socket-outlet, IB6 series,
3 poles + N + PE, 4 h (yellow), 32 A, 100 ÷
130 V, sectionable fuse carrier 10 x 38 mm

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | KI...IB6 |
| N. of poles | 3 poles + N +  |
| Clock position | 4 |
| Size | 114x228 fixing plates FC xx41 TB |
| Cable entry | M25 |
| Specification | Sectionable fuse carrier 10 x 38 mm |

Technical data

| | |
|--------------------------------|-------------|
| Current | 32 A |
| Voltage | 100 ÷ 130 V |
| IP degree of protection | IP66 |

Further technical details

| | |
|--|-----------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|---------------|--------------------------------|
| Colour | RAL 7035 grey, RAL 1021 yellow |
|---------------|--------------------------------|

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747199582 |
|-------------------|---------------|

Part number

KI 3245 IB6



Notes