


Part number

KI 3275 IB6



Interlocked switched socket-outlet, IB6 series, 3 poles + N + PE, 7 h (black), 32 A, 200/346 ÷ 240/415 V, sectionable fuse carrier 10 x 38 mm

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7035 grey, RAL 9001 black
Series	KI...IB6		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles + N + 	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Clock position	7	China RoHs - EFUP	50
Cable entry	M25	REACH SVHC substances	Yes Lead
Specification	Sectionable fuse carrier 10 x 38 mm		
Technical data		General ordering information	
Current	32 A	EAN13 code	8015747233743
Voltage	480 ÷ 500 V	Packaging Information	
IP degree of protection	IP66	Packaging length	560,00 mm
		Packaging height	330,00 mm
		Packaging width	270,00 mm
		Packaging weight	10,00 kg
		Packaging volume	49,90 dm ³
		Packaging description	Carton box
		Packaging quantity	8 Pcs
		Packaging EAN code	8015747233750
		Sub-packaging length	270,00 mm
		Sub-packaging height	125,00 mm
		Sub-packaging width	120,00 mm
		Sub-packaging weight	1,25 kg
		Sub-packaging volume	4,05 dm ³
		Sub-packaging description	Carton box
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747233767
Further technical details			
Weight	1.000,00 g		
Operating temperature range (min, max)	-25°C ... +40°C		
IK rating (impact degree of protection)	IK10		

Part number

KI 3275 IB6



Notes