


Part number

KI 3294 IB6



Interlocked switched socket-outlet, IB6 series,
3 poles + PE, 9 h (blue), 32 A, 200 ÷ 250 V,
sectionable fuse carrier 10 x 38 mm

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7035 grey, RAL 5015 blue
Series	KI...IB6		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles + 	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Clock position	9	China RoHs - EFUP	50
Size	114x228 fixing plates FC xx41 TB	REACH SVHC substances	Yes Lead
Cable entry	M25	SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Specification	Sectionable fuse carrier 10 x 38 mm	Approvals / Standards	
Technical data		Reference standard	EN 60309-1, -2 e -4
Current	32 A	General ordering information	
Voltage	200 ÷ 250 V	EAN13 code	8015747199605
IP degree of protection	IP66	Packaging Information	
Further technical details		Packaging length	560,00 mm
Weight	1.230,00 g	Packaging height	330,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Packaging width	270,00 mm
IK rating (impact degree of protection)	IK10	Packaging weight	9,84 kg
		Packaging volume	49,90 dm ³
		Packaging description	Carton box
		Packaging quantity	8 Pcs
		Packaging EAN code	8015747238649
		Sub-packaging length	270,00 mm
		Sub-packaging height	125,00 mm
		Sub-packaging width	120,00 mm
		Sub-packaging weight	1,23 kg
		Sub-packaging volume	4,05 dm ³
		Sub-packaging description	Carton box
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747238656

Part number

KI 3294 IB6



Notes