

Part number

# MFVN 24 G32



Hood, LS-TYPE series, with 2 levers, M32 top cable entry without adapter, size "104.27", high construction

#### Product description

|                      |                        |
|----------------------|------------------------|
| <b>Product type</b>  | Hood                   |
| <b>Series</b>        | LS-TYPE                |
| <b>Closing type</b>  | With 2 levers          |
| <b>Size</b>          | Size 104.27            |
| <b>Cable entry</b>   | Top cable entry<br>M32 |
| <b>Specification</b> | High construction      |

#### Technical data

|                                |      |
|--------------------------------|------|
| <b>IP degree of protection</b> | IP65 |
|--------------------------------|------|

#### Further technical details

|   |                |
|---|----------------|
| <b>Weight</b>                                 | 360,00 g       |
| <b>Operating temperature range (min, max)</b> | -40°C...+125°C |

#### Material properties

|                              |                                      |
|------------------------------|--------------------------------------|
| <b>Other materials</b>       | Lever: Polyamide (PA)<br>Gasket: NBR |
| <b>Colour</b>                | RAL 9005 black                       |
| <b>RoHs conformity</b>       | Compliant                            |
| <b>China RoHs - EFUP</b>     | E                                    |
| <b>REACH SVHC substances</b> | No                                   |

#### Approvals / Standards

|                       |         |
|-----------------------|---------|
| <b>Certifications</b> | DNV, BV |
| <b>UL</b>             | ECBT2   |
| <b>cUL</b>            | ECBT8   |

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747187428 |
| <b>eCl@ss 8.1</b> | 27440202      |
| <b>ETIM 7.0</b>   | EC000437      |


#### Packaging Information

|                                  |                   |
|----------------------------------|-------------------|
| <b>Sub-packaging weight</b>      | 1,80 kg           |
| <b>Sub-packaging description</b> | Plastic packaging |
| <b>Sub-packaging quantity</b>    | 5 Pcs             |
| <b>Sub-packaging EAN barcode</b> | 8015747188173     |

# Part number MFVN 24 G32



Catalogue drawings



Catalogue drawings

| CH..N - MF..N enclosures  |   | size "104.27"            | LS-TYPE version |
|---|---|--------------------------|-----------------|
| <p>inserts: page</p> <p>CD ..... 64 poles + @ 51+53 *</p> <p>CDD ..... 108 poles + @ 64+66 *</p> <p>CQE ..... 46 poles + @ 83+85 *</p> <p>CSH ..... 24 poles + @ 91+93 *</p> <p>CCE ..... 24 poles + @ 100+104 *</p> <p>CNE, CSE, JONE, JCSE 24 poles + @ 101 and 109 *</p> <p>CSS ..... 24 poles + @ 121+123 *</p> <p>CMSE ..... 10+2 (aux) poles + @ 139 *</p> <p>CMCE ..... 10+2 (aux) poles + @ 138 *</p> <p>CX ..... 4/8 poles + @ 155 *</p> <p>MIXO ..... 6 modules 160+195 *</p> <p>insert centre distance: 104 x 27 mm</p> <p>* refer to catalogue page CN.12</p> |   | <p>hoods with 4 pegs</p> | <p>covers</p>   |
| description   | part no.  | entry                    | part no.        |
| with 2 levers and gasket, top entry   | MHVN 24 G32   | 32                       | CHCN 24         |
| with 2 levers and gasket, top entry, high construction  | MFVN 24 G32   | 32                       | CHCN 24 G       |
| covers with pegs  |   |                          |                 |
| covers with 2 levers  |   |                          |                 |
| <p>dimensions in mm</p> <p><b>MHVN 24 G32</b></p> <p><b>MFVN 24 G32</b></p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder<br/>                     - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>  | <p>dimensions in mm</p> <p><b>CHCN 24</b></p> <p><b>CHCN 24 G</b></p> |                          |                 |
| <p>IP65</p> <p>dimensions shown are not binding and may be changed without notice</p>   |   |                          |                 |

## Notes