

Part number

MHVN 10 G25



Hood, LS-TYPE series, with 2 levers, M25 top cable entry, size "57.27"

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 2 levers
Size	Size 57.27
Cable entry	Top cable entry M25

Technical data

IP degree of protection IP65

Further technical details

Weight	161,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Other materials	Lever: Polyamide (PA) Gasket: NBR
Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747194365
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information


Sub-packaging weight	0,81 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747194372

Part number

MHVN 10 G25



Catalogue drawings



Catalogue drawings

CH..N - MF..N enclosures size "57.27" LS-TYPE version

<p>inserts: page</p> <p>CDD 42 poles + @ 61 *</p> <p>CQE 18 poles + @ 81 *</p> <p>CSH 10 poles + @ 89 *</p> <p>CCE 10 poles + @ 90 *</p> <p>CNE, CSE, JONE, JCSE: 10 poles + @ 97 and 107 *</p> <p>CSS 10 poles + @ 119 *</p> <p>CMSE 3+2 (aux) poles + @ 135 *</p> <p>CMCE 3+2 (aux) poles + @ 134 *</p> <p>CX 8/24 poles + @ 151 *</p> <p>MIXO 3 modules 160-195 *</p> <p>insert centre distance: 57 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	<p>hoods with 4 pegs</p>	<p>covers</p>
description	part no. entry	part no.
with 2 levers and gasket, top entry	MHVN 10 G25 25	
with 2 levers and gasket, top entry, high construction	MFVN 10 G32 32	
covers with pegs		CHCN 10
covers with 2 levers		CHCN 10 G
<p>dimensions in mm</p> <p>MHVN 10 G25</p> <p>MFVN 10 G32</p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>	<p>dimensions in mm</p> <p>CHCN 10</p> <p>CHCN 10 G</p>	
dimensions shown are not binding and may be changed without notice		

Notes