

Part number

MHVN 24 G32



Hood, LS-TYPE series, with 2 levers, M32 top cable entry, size "104.27"

Product description		Material properties	
Product type	Hood	Other materials	Lever: Polyamide (PA) Gasket: NBR
Series	LS-TYPE	Colour	RAL 9005 black
Closing type	With 2 levers	RoHs conformity	Compliant
Size	Size 104.27	China RoHs - EFUP	E
Cable entry	Top cable entry M32	REACH SVHC substances	No
Technical data		Approvals / Standards	
IP degree of protection	IP65	Certifications	DNV, BV
Further technical details		UL	ECBT2
Weight	248,00 g	cUL	ECBT8
Operating temperature range (min, max)	-40°C...+125°C	General ordering information	
		EAN13 code	8015747194402
		eCl@ss 8.1	27440202
		ETIM 7.0	EC000437
		Packaging Information	
		Sub-packaging weight	1,24 kg
		Sub-packaging description	Plastic packaging
		Sub-packaging quantity	5 Pcs
		Sub-packaging EAN barcode	8015747194419

Part number MHVN 24 G32



Catalogue drawings



Catalogue drawings

CH..N - MF..N enclosures		size "104.27"	LS-TYPE version
<p>inserts: page</p> <p>CD 64 poles + @ 51+53 *</p> <p>CDD 108 poles + @ 64+66 *</p> <p>CQE 46 poles + @ 83+85 *</p> <p>CSH 24 poles + @ 91+93 *</p> <p>CCE 24 poles + @ 100+104 *</p> <p>CNE, CSE, JONE, JCSE 24 poles + @ 101 and 109 *</p> <p>CSS 24 poles + @ 121+123 *</p> <p>CMSE 10+2 (aux) poles + @ 139 *</p> <p>CMCE 10+2 (aux) poles + @ 138 *</p> <p>CX 4/8 poles + @ 155 *</p> <p>MIXO 6 modules 160+195 *</p> <p>insert centre distance: 104 x 27 mm</p> <p>* refer to catalogue page CN.12</p>		<p>hoods with 4 pegs</p>	<p>covers</p>
description	part no.	entry	part no.
with 2 levers and gasket, top entry	MHVN 24 G32	32	CHCN 24
with 2 levers and gasket, top entry, high construction	MFVN 24 G32	32	CHCN 24 G
covers with pegs			
covers with 2 levers			
	<p>dimensions in mm</p> <p>MHVN 24 G32</p> <p>MFVN 24 G32</p>		<p>dimensions in mm</p> <p>CHCN 24</p> <p>CHCN 24 G</p>
<p>- kiln powder coating with RAL 9005 black epoxy polyester powder</p> <p>- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>			
<p>IP65</p> <p>dimensions shown are not binding and may be changed without notice</p>			

Notes