


Part number

PE 3245 SV



Mobile plug, PLUSO series, 3 poles + N + PE, 4 h (yellow), 32 A, 57/100 ÷ 75/130 V, straight

Product description		Material properties	
Product type	Plug Mobile	Colour	RAL 7035 grey, RAL 1021 yellow
Series	PE...SV, PLUSO	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles + N + 	China RoHs - EFUP	50
Clock position	4	REACH SVHC substances	Yes Lead
Specification	Straight	SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade
Technical data		Approvals / Standards	
Current	32 A	Reference standard	EN 60309-1 and -2
Voltage	57/100 ÷ 75/130 V	General ordering information	
IP degree of protection	IP44	EAN13 code	8015747067058
Further technical details		Packaging Information	
Weight	217,00 g	Packaging length	255,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Packaging height	195,00 mm
		Packaging width	245,00 mm
		Packaging weight	2,42 kg
		Packaging volume	12,18 dm ³
		Packaging description	Carton box
		Packaging quantity	10 Pcs
		Packaging EAN code	8015747067065


Part number

PE 3245 SV



Catalogue drawings

(16 / 32A) PE ... SV



PE ... SV		A	B	Ø min	Ø max
16A	2P+⊕	143,5	59	7	17
	3P+⊕	148,5	66	7	17
	3P+N+⊕	167,5	75	9	22
32A	2P+⊕	187	80	9	22
	3P+⊕	187	80	9	22
	3P+N+⊕	192,5	87	9	22

Notes