


Part number

# PE 3275 SV



Mobile plug, PLUSO series, 3 poles + N + PE, 7 h (black), 32 A, 277/480 ÷ 288/500 V, straight

| Product description                           |   | Material properties          |   |
|---|---|------------------------------|---|
| <b>Product type</b>                           | Plug<br>Mobile  | <b>Colour</b>                | RAL 7035 grey, RAL 9005 black   |
| <b>Series</b>                                 | PE...SV, PLUSO  | <b>RoHs conformity</b>       | Compliant with exemption<br>6(c): copper alloy containing up to 4% lead by weight |
| <b>N. of poles</b>                            | 3 poles + N +  | <b>China RoHs - EFUP</b>     | 50  |
| <b>Clock position</b>                         | 7   | <b>REACH SVHC substances</b> | Yes<br>Lead   |
| <b>Specification</b>                          | Straight  | <b>SCIP number</b>           | Ca7de37f-add8-4b77-9861-279c94903ade  |
| Technical data                                |   | Approvals / Standards        |   |
| <b>Current</b>                                | 32 A  | <b>Reference standard</b>    | EN 60309-1 and -2   |
| <b>Voltage</b>                                | 277/480 ÷ 288/500 V   | General ordering information |   |
| <b>IP degree of protection</b>                | IP44  | <b>EAN13 code</b>            | 8015747067904   |
| Further technical details                     |   | Packaging Information        |   |
| <b>Weight</b>                                 | 217,00 g  | <b>Packaging length</b>      | 255,00 mm   |
| <b>Operating temperature range (min, max)</b> | -25°C ... +40°C   | <b>Packaging height</b>      | 195,00 mm   |
|   |   | <b>Packaging width</b>       | 245,00 mm   |
|   |   | <b>Packaging weight</b>      | 2,27 kg   |
|   |   | <b>Packaging volume</b>      | 12,18 dm <sup>3</sup>   |
|   |   | <b>Packaging description</b> | Carton box  |
|   |   | <b>Packaging quantity</b>    | 10 Pcs  |
|   |   | <b>Packaging EAN code</b>    | 8015747124041   |

Part number

# PE 3275 SV



Catalogue drawings

(16 / 32A) PE ... SV



| PE ... SV       | A      | B     | Ø min | Ø max |    |
|-----------------|--------|-------|-------|-------|----|
| <b>16A</b> 2P+⊕ | 143,5  | 59    | 7     | 17    |    |
|                 | 3P+⊕   | 148,5 | 66    | 7     | 17 |
|                 | 3P+N+⊕ | 167,5 | 75    | 9     | 22 |
| <b>32A</b> 2P+⊕ | 187    | 80    | 9     | 22    |    |
|                 | 3P+⊕   | 187   | 80    | 9     | 22 |
|                 | 3P+N+⊕ | 192,5 | 87    | 9     | 22 |

Notes