


Part number

PEW 1665 SA



Mobile plug, PLUSO series, 3 poles + N + PE, 6 h (red), 16 A, 380 ÷ 415 V, angled

Product description		Material properties	
Product type	Plug Mobile	Colour	RAL 7035 grey, RAL 3000 red
Series	PEW...SA, PLUSO	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
Connection type	Screw terminal connection	China RoHs - EFUP	50
N. of poles	3 poles + N + 	REACH SVHC substances	Yes Lead
Clock position	6	SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade
Specification	Angled	Approvals / Standards	
Technical data		Reference standard	EN 60309-1 and -2
Current	16 A	General ordering information	
Voltage	380 ÷ 415 V	EAN13 code	8015747073059
IP degree of protection	IP67	Packaging Information	
Further technical details		Packaging length	285,00 mm
Weight	172,60 g	Packaging height	170,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Packaging width	190,00 mm
		Packaging weight	2,20 kg
		Packaging volume	9,21 dm ³
		Packaging description	Carton box
		Packaging quantity	10 Pcs
		Packaging EAN code	8015747073066

Part number

PEW 1665 SA



Catalogue drawings

(16 / 32A) PEW ... SA



PEW ... SA	A	B	C	Pg Ø	
16A 2P+⊕	100	77	59	13,5	
	3P+⊕	100	84	68	16
	3P+N+⊕	106	91	77	16
32A 2P+⊕	131	100	82	21	
	3P+⊕	131	100	82	21
	3P+N+⊕	131	107	93	21

Notes