


Part number

# PEW 1695 PV



Mobile socket outlet, PLUSO series, 3 poles + N + PE, 9 h (blue), 16 A, 120/208 ÷ 144/250 V

## Product description

|                        |   |
|------------------------|---|
| <b>Product type</b>    | Socket<br>Mobile  |
| <b>Series</b>          | PEW...PV, PLUSO   |
| <b>Connection type</b> | Screw terminal connection   |
| <b>N. of poles</b>     | 3 poles + N +  |
| <b>Clock position</b>  | 9   |

## Technical data

|                                |                     |
|--------------------------------|---------------------|
| <b>Current</b>                 | 16 A                |
| <b>Voltage</b>                 | 120/208 ÷ 144/250 V |
| <b>IP degree of protection</b> | IP67                |

## Further technical details

|   |                 |
|---|-----------------|
| <b>Weight</b>                                 | 225,00 g        |
| <b>Operating temperature range (min, max)</b> | -25°C ... +40°C |

## Material properties

|                              |  |
|------------------------------|--|
| <b>Colour</b>                | RAL 7035 grey, RAL 5015 blue   |
| <b>RoHs conformity</b>       | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| <b>China RoHs - EFUP</b>     | 50   |
| <b>REACH SVHC substances</b> | Yes<br>Lead  |
| <b>SCIP number</b>           | Ca7de37f-add8-4b77-9861-279c94903ade   |

## Approvals / Standards

|                           |                   |
|---------------------------|-------------------|
| <b>Reference standard</b> | EN 60309-1 and -2 |
|---------------------------|-------------------|

## General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747073967 |
|-------------------|---------------|

## Packaging Information

|                              |                       |
|------------------------------|-----------------------|
| <b>Packaging length</b>      | 255,00 mm             |
| <b>Packaging height</b>      | 195,00 mm             |
| <b>Packaging width</b>       | 245,00 mm             |
| <b>Packaging weight</b>      | 2,48 kg               |
| <b>Packaging volume</b>      | 12,18 dm <sup>3</sup> |
| <b>Packaging description</b> | Carton box            |
| <b>Packaging quantity</b>    | 10 Pcs                |
| <b>Packaging EAN code</b>    | 8015747073974         |


Part number

# PEW 1695 PV



Catalogue drawings

(16 / 32A) PEW ... PV



| PEW...PV        | A   | B   | ø min | ø max |
|-----------------|-----|-----|-------|-------|
| <b>16A</b> 2P+⊕ | 145 | 77  | 7     | 16    |
| 3P+⊕            | 145 | 85  | 7     | 16    |
| 3P+N+⊕          | 145 | 93  | 8     | 24    |
| <b>32A</b> 2P+⊕ | 162 | 97  | 8     | 24    |
| 3P+⊕            | 162 | 97  | 8     | 24    |
| 3P+N+⊕          | 162 | 105 | 8     | 24    |

Notes