


Part number

PEW 6355 PV



Mobile socket outlet, PLUSO series, 3 poles + N + PE, 5 h (black), 63 A, 347/600 ÷ 400/690 V

Product description

| | |
|-----------------------|---|
| Product type | Socket Mobile |
| Series | PEW...PV, PLUSO |
| N. of poles | 3 poles + N +  |
| Clock position | 5 |

Technical data

| | |
|--------------------------------|---------------------|
| Current | 63 A |
| Voltage | 347/600 ÷ 400/690 V |
| IP degree of protection | IP67 |

Further technical details

| | |
|---|-----------------|
| Weight | 908,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 9005 black |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ca7de37f-add8-4b77-9861-279c94903ade |

Approvals / Standards

| | |
|---------------------------|-------------------|
| Reference standard | EN 60309-1 and -2 |
|---------------------------|-------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747077262 |
|-------------------|---------------|

Packaging Information

| | |
|------------------------------|----------------------|
| Packaging length | 300,00 mm |
| Packaging height | 130,00 mm |
| Packaging width | 200,00 mm |
| Packaging weight | 2,01 kg |
| Packaging volume | 7,80 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 2 Pcs |
| Packaging EAN code | 8015747077279 |

Part number

PEW 6355 PV



Catalogue drawings

(63 / 125A) PEW ... PV



| PEW ... PV | | A | B | Pg Ø |
|-------------|--------|-----|-------|--------|
| 63A | 2P+⊕ | 277 | 108,5 | 36 |
| | 3P+⊕ | 277 | 108,5 | 36 |
| | 3P+N+⊕ | 277 | 108,5 | 36 |
| 125A | 2P+⊕ | 324 | 120,5 | 2" gas |
| | 3P+⊕ | 324 | 120,5 | 2" gas |
| | 3P+N+⊕ | 324 | 120,5 | 2" gas |

Notes