


Part number

PK 3235 PB5



Interlocked switched socket-outlet, PK series,
3 poles + N + PE, 3 h (red), 32 A, 220/380 V,
E33 - DIII fuse carrier

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | PK..PB5 |
| N. of poles | 3 poles + N +  |
| Clock position | 3 |
| Specification | E33 - DIII fuse carrier |

Technical data

| | |
|--------------------------------|---------------------------------|
| Current | 32 A |
| Voltage | 220/380V (50Hz) 250/440V (60Hz) |
| IP degree of protection | IP55 |

Further technical details

| | |
|--|-----------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|---------------|-----------------------------|
| Colour | RAL 7035 grey, RAL 3000 red |
|---------------|-----------------------------|

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information



| | |
|-------------------|---------------|
| EAN13 code | 8015747158916 |
|-------------------|---------------|

Part number

PK 3235 PB5



Catalogue drawings



| | A |
|---------------|------------|
| 2P+⊕ | 363 |
| 3P+⊕ | 370 |
| 3P+N+⊕ | 370 |

Notes