


Part number

# PK 6394 EB



Interlocked switched socket-outlet, PK series, 3 poles + PE, 9 h (blue), 63 A, 200 ÷ 250 V, without fuse-carrier

|  |   |                                     |  |
|--|---|-------------------------------------|--|
| <b>Product description</b>                     |   | <b>Material properties</b>          |  |
| <b>Product type</b>                            | Interlocked switched socket-outlet  | <b>Colour</b>                       | RAL 7035 grey, RAL 5015 blue   |
| <b>Series</b>                                  | PK..EB  |                                     | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| <b>N. of poles</b>                             | 3 poles +  | <b>RoHs conformity</b>              | 50   |
| <b>Clock position</b>                          | 9   | <b>China RoHs - EFUP</b>            | 50   |
| <b>Size</b>                                    | 114x228 fixing plates FC xx41 TB  | <b>REACH SVHC substances</b>        | Yes  |
| <b>Cable entry</b>                             | Pg29  |                                     | Lead   |
| <b>Specification</b>                           | Without fuse-carrier  | <b>SCIP number</b>                  | F6799547-ab84-42f2-938f-233ba663766d   |
| <b>Technical data</b>                          |   | <b>Approvals / Standards</b>        |  |
| <b>Current</b>                                 | 63 A  | <b>Reference standard</b>           | EN 60309-1, -2 e -4  |
| <b>Voltage</b>                                 | 200 ÷ 250 V   | <b>General ordering information</b> |  |
| <b>IP degree of protection</b>                 | IP44  | <b>EAN13 code</b>                   | 8015747082969  |
| <b>Further technical details</b>               |   | <b>Packaging Information</b>        |  |
| <b>Weight</b>                                  | 1.840,00 g  | <b>Sub-packaging length</b>         | 290,00 mm  |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C   | <b>Sub-packaging height</b>         | 125,00 mm  |
| <b>IK rating (impact degree of protection)</b> | IK10  | <b>Sub-packaging width</b>          | 155,00 mm  |
|  |   | <b>Sub-packaging weight</b>         | 1,84 kg  |
|  |   | <b>Sub-packaging volume</b>         | 5,62 dm <sup>3</sup>   |
|  |   | <b>Sub-packaging description</b>    | Carton box   |
|  |   | <b>Sub-packaging quantity</b>       | 1 Pcs  |
|  |   | <b>Sub-packaging EAN barcode</b>    | 8015747082976  |

Part number

# PK 6394 EB



## Catalogue drawings



---

Notes