


Part number

# PN 1664 PV



Mobile socket outlet, PLUSO LS-TYPE series, 3 poles + PE, 6 h (red), 16 A, 380 ÷ 415 V

#### Product description

<b>Product type</b>	Socket Mobile
<b>Series</b>	PN...PV, PLUSO LS-TYPE
<b>Connection type</b>	Screw terminal connection
<b>N. of poles</b>	3 poles + 
<b>Clock position</b>	6

#### Technical data

<b>Current</b>	16 A
<b>Voltage</b>	380 ÷ 415 V
<b>IP degree of protection</b>	IP44

#### Further technical details

<b>Weight</b>	135,00 g
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C

#### Material properties

<b>Colour</b>	RAL 9005 black
<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>China RoHs - EFUP</b>	50
<b>REACH SVHC substances</b>	Yes Lead
<b>SCIP number</b>	Ca7de37f-add8-4b77-9861-279c94903ade

#### Approvals / Standards

<b>Reference standard</b>	EN 60309-1 and -2
---------------------------	-------------------

#### General ordering information

<b>EAN13 code</b>	8015747198707
-------------------	---------------

#### Packaging Information

<b>Packaging length</b>	400,00 mm
<b>Packaging height</b>	310,00 mm
<b>Packaging width</b>	670,00 mm
<b>Packaging weight</b>	13,60 kg
<b>Packaging volume</b>	83,08 dm <sup>3</sup>
<b>Packaging description</b>	Carton box
<b>Packaging quantity</b>	100 Pcs
<b>Packaging EAN code</b>	8015747198714


Part number

# PN 1664 PV



Catalogue drawings

(16A) PN ... PV



PN...PV	A	B	Ø min	Ø max
16A 2P+⊕	146	74,5	7	16
3P+⊕	146	84,5	7	16
3P+N+⊕	146	92,5	8	24

Notes