


Part number

# TM 1674 SP



Interlocked switched socket-outlet, TM series, 3 poles + PE, 7 h (black), 16 A, 480 ÷ 500 V, without fuse-carrier, with base box

Product description	
<b>Product type</b>	Interlocked switched socket-outlet
<b>Series</b>	TM..SP/KSP
<b>N. of poles</b>	3 poles + 
<b>Clock position</b>	7
<b>Specification</b>	Without fuse-carrier With base box
Technical data	
<b>Current</b>	16 A
<b>Voltage</b>	480 ÷ 500 V
<b>IP degree of protection</b>	IP66 / IP67
Further technical details	
<b>Weight</b>	1.345,00 g
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C
<b>UL 94 flammability rating</b>	V-2
<b>IK rating (impact degree of protection)</b>	IK10

Material properties	
<b>Colour</b>	RAL 7012 grey, RAL 9005 black
<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>China RoHs - EFUP</b>	50
<b>REACH SVHC substances</b>	Yes Lead
<b>SCIP number</b>	Ce861c8d-b979-403b-96d9-80aef6dc281d
Approvals / Standards	
<b>Reference standard</b>	EN 60309-1, -2 e -4
General ordering information	
<b>EAN13 code</b>	8015747100441
Packaging Information	
<b>Sub-packaging weight</b>	1,35 kg
<b>Sub-packaging description</b>	Plastic packaging
<b>Sub-packaging quantity</b>	1 Pcs
<b>Sub-packaging EAN barcode</b>	8015747186391

Part number

# TM 1674 SP



Catalogue drawings



	A	B
<b>2P+<math>\oplus</math></b>	133	276
<b>3P+<math>\oplus</math></b>	135	276
<b>3P+N+<math>\oplus</math></b>	140	277

Notes