

Part number

TM 3234KSP



Interlocked switched socket-outlet, TM series,
3 poles + PE, 3 h (red), 32 A, 380 ÷ 380 V,
without fuse-carrier, with base box

| Product description | | Material properties | |
|--|---------------------------------------|----------------------------------|--|
| Product type | Interlocked switched socket-outlet | Colour | RAL 7012 grey, RAL 3000 red |
| Series | TM..SP/KSP | | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles | 3 poles + | RoHs conformity | 50 |
| Clock position | 3 | China RoHs - EFUP | 50 |
| Specification | Without fuse-carrier With base box | REACH SVHC substances | Yes Lead |
| Technical data | | SCIP number | Ce861c8d-b979-403b-96d9-80aef6dc281d |
| Current | 32 A | Approvals / Standards | |
| Voltage | 380V (50Hz.) 440V (60Hz.) | Reference standard | EN 60309-1, -2 e -4 |
| IP degree of protection | IP66 / IP67 | General ordering information | |
| Further technical details | | EAN13 code | 8015747137188 |
| Weight | 1.400,00 g | Packaging Information | |
| Operating temperature range (min, max) | -25°C ... +40°C | Packaging length | 385,00 mm |
| UL 94 flammability rating | V-2 | Packaging height | 320,00 mm |
| IK rating (impact degree of protection) | IK10 | Packaging width | 485,00 mm |
| | | Packaging weight | 12,60 kg |
| | | Packaging volume | 59,75 dm ³ |
| | | Packaging description | Carton box |
| | | Packaging quantity | 9 Pcs |
| | | Packaging EAN code | 8015747137249 |
| | | Sub-packaging weight | 1,40 kg |
| | | Sub-packaging description | Carton tray |
| | | Sub-packaging quantity | 1 Pcs |
| | | Sub-packaging EAN barcode | 8015747137256 |

Part number

TM 3234KSP



Catalogue drawings



| | A | B |
|---------------------------------|-----|-----|
| 2P+\oplus | 133 | 276 |
| 3P+\oplus | 135 | 276 |
| 3P+N+\oplus | 140 | 277 |

Notes