

Part number

TM 3244KIR



Interlocked switched socket-outlet, TM series, 3 poles + PE, 4 h (yellow), 32 A, 100 ÷ 130 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, with base box

Product description

Product type	Interlocked switched socket-outlet
Series	TM..IR/KIR
N. of poles	3 poles +
Clock position	4
Size	115 x 450 x 18 mm
Specification	With compartment for modular units, 4,5 DIN-rail modules EN 60715 With base box

Technical data

Current	32 A
Voltage	100 ÷ 130 V
IP degree of protection	IP66 / IP67

Further technical details

Weight	1.410,00 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-2
IK rating (impact degree of protection)	IK10

Material properties

Colour	RAL 7012 grey, RAL 1021 yellow
---------------	--------------------------------

Approvals / Standards

Reference standard	EN 60309-1, -2 e -4
---------------------------	---------------------

General ordering information


EAN13 code	8015747126489
-------------------	---------------

Part number

TM 3244KIR



Catalogue drawings



	A	B
2P+⊕	133	276
3P+⊕	135	276
3P+N+⊕	140	277

Notes