


Part number

# TM 3244KSIR



Interlocked switched socket-outlet, TM series, 3 poles + PE, 4 h (yellow), 32 A, 100 ÷ 130 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, without base box

| Product description                            |   | Material properties              |  |
|--|---|----------------------------------|--|
| <b>Product type</b>                            | Interlocked switched socket-outlet  | <b>Colour</b>                    | RAL 7012 grey, RAL 1021 yellow   |
| <b>Series</b>                                  | TM..SIR/KSIR  |                                  | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| <b>N. of poles</b>                             | 3 poles +  | <b>RoHs conformity</b>           |  |
| <b>Clock position</b>                          | 4   | <b>China RoHs - EFUP</b>         | 50   |
| <b>Size</b>                                    | 114 x 255 mm fixing distance, for assembly in single or multiple boxes                      | <b>REACH SVHC substances</b>     | Yes<br>Lead  |
| <b>Specification</b>                           | With compartment for modular units, 4,5 DIN-rail modules EN 60715<br>Without base box       | <b>SCIP number</b>               | Ce861c8d-b979-403b-96d9-80aef6dc281d   |
| Technical data                                 |   | Approvals / Standards            |  |
| <b>Current</b>                                 | 32 A  | <b>Reference standard</b>        | EN 60309-1, -2 e -4  |
| <b>Voltage</b>                                 | 100 ÷ 130 V   | General ordering information     |  |
| <b>IP degree of protection</b>                 | IP66 / IP67   | <b>EAN13 code</b>                | 8015747126502  |
| Further technical details                      |   | Packaging Information            |  |
| <b>Weight</b>                                  | 1.135,00 g  | <b>Packaging length</b>          | 385,00 mm  |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C   | <b>Packaging height</b>          | 320,00 mm  |
| <b>UL 94 flammability rating</b>               | V-2   | <b>Packaging width</b>           | 485,00 mm  |
| <b>IK rating (impact degree of protection)</b> | IK10  | <b>Packaging weight</b>          | 10,62 kg   |
|  |   | <b>Packaging volume</b>          | 59,75 dm <sup>3</sup>  |
|  |   | <b>Packaging description</b>     | Carton box   |
|  |   | <b>Packaging quantity</b>        | 9 Pcs  |
|  |   | <b>Packaging EAN code</b>        | 8015747126601  |
|  |   | <b>Sub-packaging length</b>      | 95,00 mm   |
|  |   | <b>Sub-packaging height</b>      | 40,00 mm   |
|  |   | <b>Sub-packaging width</b>       | 253,00 mm  |
|  |   | <b>Sub-packaging weight</b>      | 1,18 kg  |
|  |   | <b>Sub-packaging volume</b>      | 0,96 dm <sup>3</sup>   |
|  |   | <b>Sub-packaging description</b> | Carton tray  |
|  |   | <b>Sub-packaging quantity</b>    | 1 Pcs  |
|  |   | <b>Sub-packaging EAN barcode</b> | 8015747126618  |

Part number

# TM 3244KSIR



## Catalogue drawings



|               | <b>A</b> |
|---------------|----------|
| <b>2P+⊕</b>   | 96       |
| <b>3P+⊕</b>   | 96       |
| <b>3P+N+⊕</b> | 101      |

---

Notes