


Part number

TM 3295 SP



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 9 h (blue), 32 A, 120/208 ÷ 144/250 V, without fuse-carrier, with base box

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7012 grey, RAL 5015 blue
Series	TM..SP/KSP	Approvals / Standards	
N. of poles	3 poles + N + 	Reference standard	EN 60309-1, -2 e -4
Clock position	9	General ordering information	
Size	145 x 565 x 18 mm	EAN13 code	8015747100519
Specification	Without fuse-carrier With base box	Packaging Information	
Technical data		Sub-packaging length	150,00 mm
Current	32 A	Sub-packaging height	188,00 mm
Voltage	120/208 ÷ 144/250 V	Sub-packaging width	430,00 mm
IP degree of protection	IP66 / IP67	Sub-packaging weight	3,06 kg
Further technical details		Sub-packaging volume	12,13 dm ³
Weight	3.060,00 g	Sub-packaging description	Carton box
Operating temperature range (min, max)	-25°C ... +40°C	Sub-packaging quantity	1 Pcs
UL 94 flammability rating	V-2	Sub-packaging EAN barcode	8015747055086
IK rating (impact degree of protection)	IK10		

Part number

TM 3295 SP



Catalogue drawings



	A
2P+⊕	162
3P+⊕	162
3P+N+⊕	169

Notes