


Part number

# TM 3295KSP



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 9 h (blue), 32 A, 120/208 ÷ 144/250 V, without fuse-carrier, with base box

<b>Product description</b>		<b>Material properties</b>	
<b>Product type</b>	Interlocked switched socket-outlet	<b>Colour</b>	RAL 7012 grey, RAL 5015 blue
<b>Series</b>	TM..SP/KSP		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>N. of poles</b>	3 poles + N + 	<b>RoHs conformity</b>	50
<b>Clock position</b>	9	<b>China RoHs - EFUP</b>	50
<b>Size</b>	115 x 450 x 18 mm	<b>REACH SVHC substances</b>	Yes Lead
<b>Specification</b>	Without fuse-carrier With base box	<b>SCIP number</b>	Ce861c8d-b979-403b-96d9-80aef6dc281d
<b>Technical data</b>		<b>Approvals / Standards</b>	
<b>Current</b>	32 A	<b>Reference standard</b>	EN 60309-1, -2 e -4
<b>Voltage</b>	120/208 ÷ 144/250 V	<b>General ordering information</b>	
<b>IP degree of protection</b>	IP66 / IP67	<b>EAN13 code</b>	8015747126342
<b>Further technical details</b>		<b>Packaging Information</b>	
<b>Weight</b>	1.450,00 g	<b>Packaging length</b>	385,00 mm
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Packaging height</b>	320,00 mm
<b>UL 94 flammability rating</b>	V-2	<b>Packaging width</b>	485,00 mm
<b>IK rating (impact degree of protection)</b>	IK10	<b>Packaging weight</b>	13,05 kg
		<b>Packaging volume</b>	59,75 dm <sup>3</sup>
		<b>Packaging description</b>	Carton box
		<b>Packaging quantity</b>	9 Pcs
		<b>Packaging EAN code</b>	8015747232814
		<b>Sub-packaging weight</b>	1,45 kg
		<b>Sub-packaging description</b>	Carton tray
		<b>Sub-packaging quantity</b>	1 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747232821

Part number

# TM 3295KSP



Catalogue drawings



	A	B
<b>2P+<math>\oplus</math></b>	133	276
<b>3P+<math>\oplus</math></b>	135	276
<b>3P+N+<math>\oplus</math></b>	140	277

Notes