


Part number

TM 6374 IT



Interlocked switched socket-outlet, TM series, 3 poles + PE, 7 h (black), 63 A, 480 ÷ 500 V, E33 - DIII fuse carrier, with base box

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7012 grey, RAL 9005 black
Series	TM.. IT		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles + 	RoHs conformity	
Clock position	7	China RoHs - EFUP	50
Specification	E33 - DIII fuse carrier With base box	REACH SVHC substances	Yes Lead
Technical data		SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Current	63 A	Approvals / Standards	
Voltage	480 ÷ 500 V	Reference standard	EN 60309-1, -2 e -4
IP degree of protection	IP66 / IP67	General ordering information	
Further technical details		EAN13 code	8015747092746
Weight	3.910,00 g	Packaging Information	
Operating temperature range (min, max)	-25°C ... +40°C	Sub-packaging length	150,00 mm
UL 94 flammability rating	V-0 (insert), V-2 (enclosure)	Sub-packaging height	188,00 mm
IK rating (impact degree of protection)	IK10	Sub-packaging width	430,00 mm
		Sub-packaging weight	3,91 kg
		Sub-packaging volume	12,13 dm ³
		Sub-packaging description	Carton box
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747108881

Part number

TM 6374 IT



Catalogue drawings



Notes