

Part number

CCMA 3.0



Male crimp contact, CC series, 16 A, turned silver plated, wire cross section 3 mm², AWG 12

Product description

| | |
|---------------------|---------------|
| Product type | Crimp contact |
| Series | CC |
| Gender | Male |

Technical data

| | |
|---------------------------|----------------------|
| Current | 16 A |
| Wire cross-section | 3,00 mm ² |
| AWG size | 12 |
| Contact type | Turned silver plated |

Further technical details

| | |
|------------------------------------|--------|
| Weight | 1,20 g |
| Conductors stripping length | 7,5 mm |

Material properties

| | |
|------------------------------|--|
| Main material | Copper alloy |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | C0979fba-9907-458f-a94a-db781440f273 |

Approvals / Standards

| | |
|-----------------------|----------|
| Certifications | CSA, EAC |
| UL | ECBT2 |

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747012416 |
| eCl@ss 8.1 | 27440204 |
| ETIM 7.0 | EC000796 |

Packaging Information

| | |
|----------------------------------|----------------------|
| Packaging length | 112,00 mm |
| Packaging height | 95,00 mm |
| Packaging width | 117,00 mm |
| Packaging weight | 1,28 kg |
| Packaging volume | 1,24 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 800 Pcs |
| Packaging EAN code | 8015747103930 |
| Sub-packaging length | 50,00 mm |
| Sub-packaging height | 44,00 mm |
| Sub-packaging width | 50,00 mm |
| Sub-packaging weight | 0,16 kg |
| Sub-packaging volume | 0,11 dm ³ |
| Sub-packaging description | Plastic box |
| Sub-packaging quantity | 100 Pcs |
| Sub-packaging EAN barcode | 8015747012423 |

Part number

CCMA 3.0



Catalogue drawings



CCF, CCM and CC..AN contacts

| conductor section mm ² | conductor slot $\varnothing A$ (mm) | conductors stripping length (mm) |
|--------------------------------------|--|-------------------------------------|
| 0,14-0,37 | 0,9 | 7,5 |
| 0,5 | 1,1 | 7,5 |
| 0,75 | 1,3 | 7,5 |
| 1,0 | 1,45 | 7,5 |
| 1,5 | 1,8 | 7,5 |
| 2,5 | 2,2 | 7,5 |
| 3 | 2,55 | 7,5 |
| 4 | 2,85 | 7,5 |