

Part number

# CHIN 10



Bulkhead mounting housing, LS-TYPE series, with 2 levers, size "57.27"

#### Product description

|                     |                           |
|---------------------|---------------------------|
| <b>Product type</b> | Bulkhead mounting housing |
| <b>Series</b>       | LS-TYPE                   |
| <b>Closing type</b> | With 2 levers             |
| <b>Size</b>         | Size 57.27                |
| <b>Cable entry</b>  | Without cable entry       |

#### Technical data

|                                |      |
|--------------------------------|------|
| <b>IP degree of protection</b> | IP65 |
|--------------------------------|------|

#### Further technical details

|   |                |
|---|----------------|
| <b>Weight</b>                                 | 86,00 g        |
| <b>Operating temperature range (min, max)</b> | -40°C...+125°C |

#### Material properties

|                              |                                      |
|------------------------------|--------------------------------------|
| <b>Other materials</b>       | Lever: Polyamide (PA)<br>Gasket: NBR |
| <b>Colour</b>                | RAL 9005 black                       |
| <b>RoHs conformity</b>       | Compliant                            |
| <b>China RoHs - EFUP</b>     | E                                    |
| <b>REACH SVHC substances</b> | No                                   |

#### Approvals / Standards

|                       |         |
|-----------------------|---------|
| <b>Certifications</b> | DNV, BV |
| <b>UL</b>             | ECBT2   |
| <b>cUL</b>            | ECBT8   |

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747163088 |
| <b>eCl@ss 8.1</b> | 27440202      |
| <b>ETIM 7.0</b>   | EC000437      |

#### Packaging Information

|                                  |                       |
|----------------------------------|-----------------------|
| <b>Packaging length</b>          | 305,00 mm             |
| <b>Packaging height</b>          | 180,00 mm             |
| <b>Packaging width</b>           | 275,00 mm             |
| <b>Packaging weight</b>          | 3,44 kg               |
| <b>Packaging volume</b>          | 15,10 dm <sup>3</sup> |
| <b>Packaging description</b>     | Carton box            |
| <b>Packaging quantity</b>        | 40 Pcs                |
| <b>Packaging EAN code</b>        | 8015747187589         |
| <b>Sub-packaging weight</b>      | 0,43 kg               |
| <b>Sub-packaging description</b> | Plastic packaging     |
| <b>Sub-packaging quantity</b>    | 5 Pcs                 |
| <b>Sub-packaging EAN barcode</b> | 8015747187596         |

# Part number CHIN 10



Catalogue drawings

Catalogue drawings

**CH.N - MA, MF.N custodie** grandezza "57.27" versione LS-TYPE

frutti inseribili: pag. **custodie fisse chiusura doppia** **custodie mobili chiusura doppia**

|                               |                          |  |  |
|-------------------------------|--------------------------|--|--|
| CDD ..... 42 poli + @         | 61 *                     |  |  |
| CDE ..... 18 poli + @         | 81 *                     |  |  |
| CSH ..... 10 poli + @         | 89 *                     |  |  |
| CCE ..... 10 poli + @         | 90 *                     |  |  |
| CNE, CSE, JONE, JCSE          | 10 poli + @ 97 and 107 * |  |  |
| CSS ..... 10 poli + @         | 119 *                    |  |  |
| CTE, CTSE *)                  | 10 poli + @ 127 *        |  |  |
| CMSE ..... 3+2 (aux) poli + @ | 135 *                    |  |  |
| CMCE ..... 3+2 (aux) poli + @ | 134 *                    |  |  |
| CX ..... 8/24 poli + @        | 151 *                    |  |  |
| MIXO ..... 3 moduli           | 160+195 *                |  |  |

interassi fissaggio frutti: 57 x 27 mm

\* riferimenti di pagina catalogo CN.12

| descrizione                          | codice articolo | uscita M | codice articolo | uscita M |
|--------------------------------------|-----------------|----------|-----------------|----------|
| custodia da incasso, con 2 leve      | CHIN 10         |          |                 |          |
| custodia da parete, alta, con 2 leve | MAPN 10.32      | 32       |                 |          |
| con pinoli, uscita orizzontale, alta |                 |          | MHON 10.25      | 25       |
| con pinoli, uscita orizzontale, alta |                 |          | MFON 10.32      | 32       |
| con pinoli, uscita verticale         |                 |          | MHVN 10.25      | 25       |
| con pinoli, uscita verticale, alta   |                 |          | MFVN 10.32      | 32       |

\*) solo nella custodia CHIN 10

dimetri di fissaggio custodia da incasso in mm

dimensioni in mm

CHIN 10

MAPN 10.32

dimensioni in mm

MFON 10.32

MHON 10.25

MHVN 10.25

- verniciatura a forno con polvere epossipoliesterale nero RAL 9005  
- leva di chiusura in materiale termoplastico auto-attingente, di colore nero RAL 9005 (leva di ricambio pag. 12)

IP65

le misure indicate non sono impegnative e possono essere variate senza alcun preavviso

6

**CH.N - MA, MF.N enclosures** size "57.27" LS-TYPE version

inserts: page **housings with double lever** **hoods with 4 pegs**

|                                |                           |  |  |
|--------------------------------|---------------------------|--|--|
| CDD ..... 42 poles + @         | 61 *                      |  |  |
| CDE ..... 18 poles + @         | 81 *                      |  |  |
| CSH ..... 10 poles + @         | 89 *                      |  |  |
| CCE ..... 10 poles + @         | 90 *                      |  |  |
| CNE, CSE, JONE, JCSE           | 10 poles + @ 97 and 107 * |  |  |
| CSS ..... 10 poles + @         | 119 *                     |  |  |
| CTE, CTSE *)                   | 10 poles + @ 127 *        |  |  |
| CMSE ..... 3+2 (aux) poles + @ | 135 *                     |  |  |
| CMCE ..... 3+2 (aux) poles + @ | 134 *                     |  |  |
| CX ..... 8/24 poles + @        | 151 *                     |  |  |
| MIXO ..... 3 modules           | 160+195 *                 |  |  |

insert centre distance: 57 x 27 mm

\* refer to catalogue page CN.12

| description  | part no.   | entry M | part no.   | entry M |
|--|------------|---------|------------|---------|
| bulkhead mounting housing, with 2 levers                   | CHIN 10    |         |            |         |
| surface mounting housing, high construction, with 2 levers | MAPN 10.32 | 32      |            |         |
| with pegs, side entry                                      |            |         | MHON 10.25 | 25      |
| with pegs, side entry, high construction                   |            |         | MFON 10.32 | 32      |
| with pegs, top entry                                       |            |         | MHVN 10.25 | 25      |
| with pegs, top entry, high construction                    |            |         | MFVN 10.32 | 32      |

\*) only in the CHIN 10 enclosure

panel cut-out for bulkhead mounting housing in mm

dimensioni in mm

CHIN 10

MAPN 10.32

dimensioni in mm

MFON 10.32

MHON 10.25

MHVN 10.25

- kin powder coating with RAL 9005 black epoxy polyester powder  
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

IP65

dimensions shown are not binding and may be changed without notice

6