

Part number

CVAP 16 LS



Surface mounting housing, V-TYPE series, with 1 lever, Pg21 cable entry, size "77.27", high construction, with metal cover

Product description

Product type	Surface mounting housing
Series	V-TYPE
Closing type	With 1 lever
Size	Size 77.27
Cable entry	With cable entry Pg21
Specification	High construction, with metal cover

Technical data

IP degree of protection IP65

Further technical details

Contact resistance	$\leq 3 \text{ m}\Omega$
Weight	1,00 g
Operating temperature range (min, max)	-40°C...+125°C
Conductors stripping length	8 mm (6 mm for 2,5 mm ²)
Torque for main contact	M2,5: 0.4 Nm; 3.5 lb.in (0,5 x 3mm)
Tightening torque for PE connection	M4: 1,2 Nm, 10,6 lb.in (Ph2 or 1,0x5,5mm)
Tightening torque for fixing screws	M3: 0.5 Nm; 4.4 lb.in (0.5x3 mm)

Material properties

Other materials	Lever: Stainless steel Gasket: NBR
Colour	RAL 7040 grey
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747149693
ETIM 7.0	EC000438

Packaging Information

Packaging description	Carton box
Packaging quantity	10 Pcs
Packaging EAN code	8015747248235
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747248242