

Part number

DPTCM 09



Male insert, D-SUB, crimp connection, 9 poles

| Product description | |
|-----------------------------------------------|--------------------------------------------------------|
| Product type | Data connector |
| Series | D-SUB |
| Connection type | Crimp connection |
| Gender | Male |
| N. of poles | 9 poles |
| Size | DE-9 |
| Technical data | |
| Current | 5 A |
| Voltage | 50 V |
| Rated impulse withstand voltage | 1 |
| Pollution degree | 3 |
| Further technical details | |
| Characteristics according to EN 61984 | With turned contacts: 7 A / with stamped contacts: 5 A |
| Insulation resistance | ≥ 10 GΩ |
| Weight | 4,50 g |
| Operating temperature range (min, max) | -55 °C ... +125 °C |
| UL 94 flammability rating | V-0 |

| Material properties | |
|----------------------------------|--------------------|
| Main material | Polycarbonate (PC) |
| RoHS conformity | Compliant |
| China RoHS - EFUP | E |
| REACH SVHC substances | No |
| General ordering information | |
| EAN13 code | 8015747287289 |
| Packaging Information | |
| Sub-packaging description | Plastic bag |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747184656 |