


Part number

JDAF 16 N



Product description

| | |
|------------------------|--|
| Product type | Insert |
| Series | JDA |
| Connection type | Screw terminal connection |
| Gender | Female |
| N. of poles | 32 poles +  |
| Size | Size "66.40" |

Technical data

| | |
|--|---|
| Current | 16 A |
| Voltage | 250 V |
| Rated impulse withstand voltage | 4 kV |
| Pollution degree | 3 |
| Wire cross-section | 0,25 mm ² - 2,50 mm ² |
| AWG size | 24 - 14 |
| Contact type | Turned tin plated |

Further technical details

| | |
|---------------|---------|
| Weight | 59,00 g |
|---------------|---------|

Approvals / Standards

| | |
|---------------------------|------------------|
| Reference standard | EN 61984:2009-06 |
|---------------------------|------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747257046 |
|-------------------|---------------|

Packaging Information

| | |
|----------------------------------|----------------------|
| Packaging length | 260,00 mm |
| Packaging height | 120,00 mm |
| Packaging width | 140,00 mm |
| Packaging weight | 1,98 kg |
| Packaging volume | 4,37 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 30 Pcs |
| Packaging EAN code | 8015747257053 |
| Sub-packaging length | 118,00 mm |
| Sub-packaging height | 32,00 mm |
| Sub-packaging width | 76,00 mm |
| Sub-packaging weight | 0,33 kg |
| Sub-packaging volume | 0,29 dm ³ |
| Sub-packaging description | Carton tray |
| Sub-packaging quantity | 5 Pcs |
| Sub-packaging EAN barcode | 8015747257060 |