

Part number  
**JKF 03**



Female insert, JK series, screw terminal connection, 3 poles + PE, 10 A 230/400 V 4 kV 3, size "21.21"

<b>Product description</b>		<b>Material properties</b>	
<b>Product type</b>	Insert	<b>Main material</b>	Polycarbonate (PC)
<b>Series</b>	JK	<b>Other materials</b>	Contacts: copper alloy
<b>Connection type</b>	Screw terminal connection	<b>Colour</b>	RAL 7035 grey
<b>Gender</b>	Female	<b>RoHs conformity</b>	Compliant with exemption 6(c); copper alloy containing up to 4% lead by weight
<b>N. of poles</b>	3 poles +	<b>China RoHs - EFUP</b>	50
<b>Size</b>	Size "21.21"	<b>REACH SVHC substances</b>	Yes Lead
<b>Technical data</b>		<b>SCIP number</b>	1a9c93ff-0445-4a16-81e3-1609ac5274d6
<b>Current</b>	10 A	<b>Approvals / Standards</b>	
<b>Voltage</b>	230 - 400 V	<b>Reference standard</b>	EN 61984:2009-06
<b>Rated impulse withstand voltage</b>	4 kV	<b>Certifications</b>	CSA, CQC, DNV, BV, EAC
<b>Pollution degree</b>	3	<b>UL</b>	ECBT2
<b>Rated voltage according to UL/CSA</b>	600V	<b>General ordering information</b>	
<b>Wire cross-section</b>	0,75 mm <sup>2</sup> - 2,50 mm <sup>2</sup>	<b>EAN13 code</b>	8015747209434
<b>AWG size</b>	18 - 14	<b>Packaging Information</b>	
<b>Contact type</b>	Turned tin plated	<b>Packaging length</b>	210,00 mm
<b>IP degree of protection</b>	IP20 without enclosure, IP44/IP66/IP67/IP68/IP69 with enclosure	<b>Packaging height</b>	200,00 mm
<b>Further technical details</b>		<b>Packaging width</b>	130,00 mm
<b>Characteristics according to EN 61984</b>	10A 230/400V 4kV 3; 10A 400/690V 4kV 2	<b>Packaging weight</b>	3,25 kg
<b>Mating cycles</b>	≥ 200	<b>Packaging volume</b>	5,46 dm <sup>3</sup>
<b>Insulation resistance</b>	≥ 10 GΩ	<b>Packaging description</b>	Carton box
<b>Weight</b>	15,75 g	<b>Packaging quantity</b>	200 Pcs
<b>Operating temperature range (min, max)</b>	-40°C ... +100°C	<b>Packaging EAN code</b>	8015747209595
<b>UL 94 flammability rating</b>	V-1	<b>Sub-packaging length</b>	197,00 mm
		<b>Sub-packaging height</b>	35,00 mm
		<b>Sub-packaging width</b>	113,00 mm
		<b>Sub-packaging weight</b>	0,65 kg
		<b>Sub-packaging volume</b>	0,78 dm <sup>3</sup>
		<b>Sub-packaging description</b>	Carton tray
		<b>Sub-packaging quantity</b>	40 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747209601