


Part number

KI 3294 IB6



Interlocked switched socket-outlet, IB6 series,
3 poles + PE, 9 h (blue), 32 A, 200 ÷ 250 V,
sectionable fuse carrier 10 x 38 mm

Product description	
Product type	Interlocked switched socket-outlet
Series	KI...IB6
N. of poles	3 poles + 
Clock position	9
Size	114x228 fixing plates FC xx41 TB
Cable entry	M25
Specification	Sectionable fuse carrier 10 x 38 mm
Technical data	
Current	32 A
Voltage	200 ÷ 250 V
IP degree of protection	IP66
Further technical details	
Weight	1.230,00 g
Operating temperature range (min, max)	-25°C ... +40°C
IK rating (impact degree of protection)	IK10

Material properties	
Colour	RAL 7035 grey, RAL 5015 blue
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Approvals / Standards	
Reference standard	EN 60309-1, -2 e -4
General ordering information	
EAN13 code	8015747199605
Packaging Information	
Packaging length	560,00 mm
Packaging height	330,00 mm
Packaging width	270,00 mm
Packaging weight	9,84 kg
Packaging volume	49,90 dm ³
Packaging description	Carton box
Packaging quantity	8 Pcs
Packaging EAN code	8015747238649
Sub-packaging length	270,00 mm
Sub-packaging height	125,00 mm
Sub-packaging width	120,00 mm
Sub-packaging weight	1,23 kg
Sub-packaging volume	4,05 dm ³
Sub-packaging description	Carton box
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747238656